M2M[1] M2M[1]FD

bradbury security

Steel Door Sizes

- Single Doors: Max Width 1220mm X Max Height 2450mm

Steel Door Frame

- Internal steel chassis system for extra strength
- Strategic reinforcing system
- Security door manufactured from 1.6mm Zintec Steel
- 90mm single rebate profile
- Integral mounting plates
- Prepared for inside and outside fixing
- P seals
- Fast fit option

Steel Door Threshold

- Disability Discrimination Act (DDA) compliant aluminium threshold

Steel Door Leaf

- Manufactured from 1.2mm Zintec Steel
- Folded 45mm thick leaf with composite Dufaylite honeycomb core

Steel Door Hinges

- Minimum of 4 high quality stainless steel hinges (BS 1935.2002 Grade 13) (larger doors have 6 hinges)

Steel Door Dog Bolts

- Minimum of 3 no. 17 mm solid steel dog bolts (9 on larger doors)

Steel Door Standard Hardware Options (included in price)

- Option A - Sashlock, lever handles and euro profile cylinder
- Option B – Deadlock, euro profile cylinder and escutcheon plates
- Option C – 14 point combat lock, lever handles and euro profile cylinder (available at a small premium)
- Option D – Briton 2 point panic bars with reinforcing
- Option E – Yale 82 rim lock with cylinder

FIRE-RATED OPTIONS ALSO AVAILABLE - CERTIFIED UP TO 240 MINUTES

LPCB Loss Prevention Certification Board
Bradbury Security M2M[1]
Assessed to LPS1175: Issue 6
Cert No. 312d
Security Rating 1

Secured by Design
SBD
Official Police Security Initiative

constructionline

CHAS
Contractors Health & Safety Assessment Scheme
Accredited Contractor
www.chas.gov.uk

bsia
british security industry association

UVDB
empowered by Achilles
Registered